MATERIAL SAFETY DATA SHEET

SPOTCHECK[®] DEVELOPER SKD-S2

IDENTIFICATION 1.

Company:	MAGNAFLUX
Address:	3624 West Lake Avenue, Glenview, Illinois 60025
Telephone No.:	847-657-5300 (Off-Hour Emergency Number - CHEMTREC - 1-800-424-9300).
Product Use:	Penetrant inspection developer
NFPA Rating:	Health 1, Flammability 3, (aerosol 4), Reactivity 0
Revision Date:	March 21, 2014
0	

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Wt./Wt.%	CAS#	TLV	PEL	LD ₅₀	LC ₅₀
2-propanol	40 - 70	67-63-0	400 ppm	400 ppm	3.6 g/kg(oral/mouse	Not available
2-propanone	10 – 30	67-64-1	750 ppm	750 ppm	6 g/kg (oral/rat)	Not available
Isobutane (propellent – aerosol only)	30	75-28-5	Not available	1000 ppm	Not available	Not available
Talc	1 - 3	14807-96-6	Not available	2 mg/me	Not available	Not available

HAZARDS IDENTIFICATION 3.

EMERGENCY OVERVIEW Extremely flammable white liquid and aerosol. Fast evaporating vapors can reach hazardous levels quickly in unventilated spaces.

POTENTIAL HEALTH EFFECTS & SIGNS AND SYMPTOMS OF EXPOSURE:

Can irritate by removing natural skin oils on long or repeated exposures. Skin Contact:

- Eyes: Irritating, but does not damage eye tissue.
- Inhalation: Causes dizziness and nausea.

Ingestion: Not significant in small (mouthful) amounts.

Medical conditions known to be aggravated by exposure to product: None

FIRST AID 4

Skin Contact:	Remove contaminated clothing. Wash exposed areas with soap and water. Use soothing lotion.		
Eyes:	Rinse carefully under upper and lower eyelids using plenty of water.		
Inhalation:	Remove to fresh air if dizzy or nauseated.		
Ingestion:	Do not induce vomiting. Accidental ingestion of a single mouthful is not expected to cause significant harm.		
NOTE: In all severe cases, contact physician immediately. Local telephone operators can furnish number of regional poison control center.			

FIRE HAZARD 5

Conditions of flammability:	Non-aerosol and aerosol: Ignition will occur if used near flames, arcs or other ignition sources.
Flash point:	2°F (-16°C) (Pensky-Martens closed cup).
Flammable limits in air:	2% to 15%.
Extinguishing media:	Carbon dioxide, foam, water.
Special fire fighting procedures:	Keep containers cool with water spray.
Hazardous combustion products:	Soot, oxides of carbon.
Unusual fire hazards:	Aerosol cans may burst over 130°F (54°C) and add to existing fire.

ACCIDENTAL RELEASE MEASURES 6.

Turn off or remove sources of ignition. Mop up or sweep up with absorbent. (For disposal, see Section 13.)

7. HANDLING AND STORAGE

Avoid breathing vapors. Avoid eye contact. Avoid repeated or prolonged skin contact. Store away from heat source. Do not spray around arcs or flame. Storage Level 2 Aerosols per NFPA 30B

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Controls: Personal protection : Use where ventilation will carry vapors away from occupied areas. Wear safety glasses to protect eyes. Wear nitrile rubber gloves if hand exposure is unavoidable. Respirator with filter if sprayed in enclosed, unventilated space.



9. PHYSICAL PROPERTIES

Initial boiling point (bulk):

Percent volatile: Density/sp. gravity: Water solubility: pH:

p....

STABILITY AND REACTIVITYStability:Stability:Incompatibility:NoHazardous decomposition products:WReactivity:No

Stable None When burning, soot, oxides of carbon None

132° F (55°C) (ASTM D-86)

90%

0.87

90 Neutral

11. <u>TOXICOLOGICAL INFORMATION</u> Carcinogenicity: Threshold limit value (Bulk): WHMIS information (Canada):

Contains no known or suspected carcinogens listed with OSHA, IARC, NTP, or ACGIH. 400 ppm According to available information, the ingredients have not been found to show reproductive toxicity, teratogenicity, mutagenicity, skin sensitization, or synergistic toxic effects with other materials.

12. ECOLOGICAL INFORMATION No data is available on SKD-S2.

13. DISPOSAL

10.

All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. U.S. EPA Waste Number: D001

14. TRANSPORTATION (These are guidelines, in all cases refer to 49 CFR for proper classification)

U.S. DOT: 49 CFR 172.101 Hazard	ous Materials Table	
	Non-Aerosol	<u>Aerosol</u>
Proper shipping name:	Flammable Liquid, n.o.s.	Consumables
	(Isopropanol, acetone)	
Hazard class or division:	3	None
Identification No.:	UN1993	None
Packing Group:	II	None
IATA: List of Dangerous Goods	Non-aerosol	Aerosol
Proper shipping name:	Flammable liquid, n.o.s.	Aerosols, flammable
	(Isopropanol, Acetone)	
Hazard class or division:	3	2.1
Identification No.:	UN1993	UN1950
Packing Group:	II	-
IMDG: General Index	Non-aerosol	Aerosol
Proper shipping name:	FLAMMABLE LIQUID, N.O.S.	AEROSOLS
	(ISOPROPANOL, ACETONE)	
Hazard class or division:	3.2	2.1
Identification No.:	UN1993	UN1950
Packing Group:	II	-

15. REGULATORY INFORMATION

16.

TSCA: CERCLA: SARA TITLE III, Section 313: California Proposition 65: All ingredients are listed in TSCA inventory. Reportable quantity (RQ) for Acetone = 5000 lbs. Acetone. This product contains trace amount of chemicals known to the State of California to cause cancer and to

 WHMIS Class (Canada):
 Non-Aerosol: B-2, D-2B - Aerosol: A, B-5, D-2B

 Note:
 This MSDS has been prepared to meet WHMIS (Canada) requirements with the exception of using 16 headings.

Bulk Aerosol 4 OTHER INFORMATION Revision Statement: Section 1 Supersedes: April 1, 2013

/AGNAFLUX

A Division of Illinois Tool Works Inc. 3624 WEST LAKE AVENUE ■ GLENVIEW, ILLINOIS 60026 TEL 847.657.5300 ■ FAX 847.657.5388 www.magnaflux.com Vapor pressure:

Vapor density: Evaporation rate: Appearance: Odor: Bulk: 150mm @ 100°F (38°C). Aerosol: 65 psi @ 75°F (24°C) 3 0.4 of ether White liquid Alcohol odor